



STERA

GBP 3136SH AB60



Cutout: 280 x 1180



Unit: cd
— C0-C180 — C90-C270 — G2.5



Product Features and Key Data

Applications :	Surgery Room - Clinics - Hospital
Luminaire Type :	LED Sterile Backlight
Mounting Method :	Recessed
Luminaire Optic :	Froasted tempered glass
Connected Load :	36W
Colour Temperature :	6000K
Rated Luminous Flux :	3240 lm
Luminous Efficiency :	90 lm/W
Power Factor :	> 0,957
CRI Value :	> 80
UGR :	< 20 (EN124664-1)
Photo Biological Class :	Group 0 - No risk
Luminaire Colour :	Ral 9016 Traffic white
Luminaire Body :	Luminaire body DKP steel. Electrostatic powder coating
Electrical version :	With electronic transformer, switchable.
Connection method :	Terminal
Mains frequency :	50/60 Hz
Mains voltage :	220 - 240 V
Led Service (25°) :	L80 = 50.000 h
Driver (220 - 240V) :	Tridonic, Osram or Gecem
Ceiling Type :	AB - Gypsum Ceiling TB - Modular Ceiling KB - Clip-in Ceiling
Ingress Protection (IP) rating :	IP65
Protection class :	I
Impact resistance (IK) :	IK07
Hot wire resistance :	650 °C
Ambient temperature :	- 20 - 35 °C
Options :	1 - 3 Hours Emergency Kit, Dali Dimmable
Accessories :	